



SAE 30

**4 Stroke Engine Oil
For vintage cars and motorcycles**

Mineral Monograde

TYPE OF USE

Especially formulated for collector and vintage cars engines and gearboxes built between 1900 and 1950.

Suitable for Gasoline or Diesel 4 stroke engines. Also suitable for collector bike engines.

PERFORMANCE

MOTUL SAE 30 is a last generation oil specially designed for old technology engines.

Mineral monograde lubricant with very low detergent level for a complete compatibility with paper ,felt and fabric gaskets.

Small detergent level avoids soot and deposits removing in the lubricating circuit.

Can be used as break-in oil if drain intervals are shortened.

Complete compatibility with nonferrous metals as brass, bronze, cooper.

Reinforced adherence for easier start even after a long period of immobilization.

RECOMMENDATIONS

Drain interval : drain at least once a year.

PROPERTIES

Viscosity grade	SAE J 300	30
Density at 20°C (68°F)	ASTM D1298	0.888
Viscosity at 40°C (104°F)	ASTM D445	106.6 mm ² /s
Viscosity at 100°C (212°F)	ASTM D445	11.7 mm ² /s
Viscosity index	ASTM D2270	97
Pour point	ASTM D97	-27°C / -16.6°F
Flash point	ASTM D92	264°C / 507.2°F
TBN	ASTM D2896	1.7 mg KOH/g